

CaWrap UV 200 FR


**UDB
USB**
for walls



CE
EN 13859-2



SYSTEMATIC SAFETY AND ENERGY EFFICIENCY



CaWrap UV 200 FR is a façade membrane designed for closed and partially open constructions. Its smooth surface allows any accumulated or penetrating moisture to run off safely and securely. The membrane consists of a polyamide (PES) non-woven material and an innovative, diffusion-open polyurethane coating that provides long-lasting UV protection. Rain and driving snow are effectively kept away from the insulation layer.

FIELDS OF APPLICATION

Curtain-type and rear-ventilated façades

Maximum joint proportion: joint proportion of up to 40% and a clear joint width of max. 50 mm

BENEFITS

UV resistance

Diffusion-open to protect insulation against driving snow and rain

Windproof black surface

Building material class Bs1 d0

TECHNICAL DATA

EN 13859-2

Weight (g/m ²)	195 - 15 + 25
Fire behavior	Bs1 d0
Water vapor permeability sd (m)	0.13 ± 0.03
Resistance to water penetration	W 1
Maximum tensile strength (L / T) (N / 5 cm)	400/320 ± 80
Elongation at maximum tensile strength (L / T) (%)	50/60 - 15 + 20
Tear resistance (nail shaft) L / T (N)	280/340 ± 80
Cold bending behaviour (°C)	< - 20
Water pressure resistance (cm WS)	> 400
Temperature range (°C)*	- 20 to + 70
Roll width / Roll length (m)	1.50/50

* Based on cold bending behavior (EN 1109) and aging temperature (EN 1296)

PROS 1 07/26 EN

The generally accepted rules of technology, the latest version of technical regulations (e.g., those of the ZVDH), the CaPlast processing instructions, and all other applicable manufacturer guidelines, rules, and standards must be observed during processing.

Version: July 2026 (all technical data sheets prior to this date are invalid)

The information contained in this document has been compiled to the best of our knowledge, and was considered to be correct at the time of publication. CaPlast is committed to continuous improvement and therefore reserves the right to change or supplement product specifications without prior notice, particularly if changes in legislation require it. No rights can be derived from this document. This document is subject to changes, typographical errors and misprints.

Note:

This document replaces all previous versions. To obtain the latest versions of the technical documentation, including the technical data sheet, declaration of performance and installation instructions, scan the QR code or use this link: <https://www.caplast.de/en/downloads>.

